

ICOM

VHF MARINE TRANSCEIVER

IC-M423G

(With GPS Receiver)

# Active Noise Cancelling Technology and Built-in GPS for Simple Installation

Optional COMMANDMIC™, HM-195GB



**Built-in GPS Receiver Simplifies Installation**



**Active Noise Cancelling for Maximum Clarity**



**Icom Marine Family User Interface & White Backlit LCD & Keypad**



**10W Loud Audio, Public Address and Foghorn**



**Optional COMMANDMIC™ HM-195GB/GW for 2nd Station/Intercom**



**Built-in Class D DSC (Meets ITU-R M493-13)**



**IPX7 Waterproof Protection (1m depth for 30 minutes)**



**Common NMEA Interface for GPS/NAV Connection**



**MarineCommander™ and MA-500TR Compatible**



**AquaQuake™ Function**



Also available in super white version

**Intuitive User Interface and White Backlit LCD and Keypad**

Incorporating Icom's common Marine Family User Interface designed for simple, intuitive operation. A rotary selector and directional keypad provide quick and easy access to the intended functions. The high contrast white backlit LCD and laser-cut keypad match well with modern boat designs.

**Active Noise Cancelling**

The built-in active noise cancelling provides superb performance. It reduces background noise up to 90% in the received signal and 30% in the transmits signal.

**10W Loud Audio, Public Address and Foghorn**

The IC-M423G has a built-in 10W amplifier that increases the audio output to an external PA speaker. The public address function allows you to make an announcement from the microphone like a loud speaker, the foghorn can also be emitted from the external PA speaker.

**Built-in Class D DSC**

The built-in DSC watch function monitors Ch. 70 (DSC channel) activity, even while you are receiving another channel. DSC functions include: distress, individual, group, all ships, urgency, safety, position request/report, polling request and DSC test calls.

**Built-in GPS Receiver**

The built-in GPS receiver shows your current position, date/time and can be used for DSC calls. The GPS data source is selectable from internal and external GPS.

**Optional White Backlit COMMANDMIC™ HM-195GB/GW**

The optional white backlit COMMANDMIC makes it convenient for using the IC-M423G from a separate cabin or tower. All functions of the IC-M423G can be controlled from the COMMANDMIC and can be used as an intercom with the IC-M423G.

**AIS Target Call with MA-500TR**

When connected to the optional MA-500TR Class B AIS transponder, the AIS target call function allows you to make an individual DSC call without having to manually input an MMSI number.







**And More**

- Simple remote control speaker-microphone, HM-205B/SW
- NMEA 0183 connectivity
- MarineCommander™ compatible
- AquaQuake™ draining function
- IPX7 waterproof protection (1m depth for 30 minutes)
- Dual/tri-watch function for monitoring Ch.16 and/or call channel
- Priority and normal scan
- Black and super white versions available.

**SPECIFICATIONS**

GENERAL		
Frequency range	Tx Rx CH70	156.000–161.450MHz 156.000–163.425MHz 156.525MHz
Usable channels		INT, USA* channels * Available depending on version
Type of emission		16K0G3E (FM), 16K0G2B (DSC)
Power supply requirement		13.8V DC nominal (10.8–15.6V DC)
Current drain (at 12.0V DC)	Tx Rx	5.5A 5.0A (RX SP ON) 1.5A
Operating temperature range		-20°C to +60°C
Antenna impedance		50Ω (SO-239)
Dimensions (W×H×D) (projections not included)		180×82×119.9mm
Weight (approx.)		1.2kg
NMEA in/out formats		RMC, GGA, GNS, GLL, DSC, DSE
TRANSMITTER		
Output power (at 12.0V DC)		25W, 1W
Max. frequency deviation		±5.0kHz
Frequency stability		Less than ±1.5kHz
Spurious emissions		Less than 0.25µW
RECEIVER		
Sensitivity (20dB SINAD)		-5dBµ emf typ.
Squelch sensitivity		Less than -2dBµ emf
Adjacent channel selectivity		More than 70dB
Spurious response		More than 70dB
Intermodulation		More than 68dB
Audio output power (at 10% distortion, 4Ω load)		More than 10W (Ext. speaker)
GPS RECEIVER		
Receiving frequency		1575.42MHz
Receiving channels		66 channels
Satellite differential type		WAAS, EGNOS, MSAS, GAGAN
Measurements made in accordance with EN 301 025-2, -3. All stated specifications are subject to change without notice or obligation.		
<b>Applicable IP Rating</b>		
<b>Ingress Protection Standard</b>		
Water		IPX7 (Waterproof protection)
<b>Supplied accessories:</b>		
• Hand microphone, HM-205B/SW • DC power cable		
• Mounting bracket kit		

**OPTIONS**

<p><b>COMMANDMIC™</b></p>  <p><b>Supplied accessories</b></p>  <ul style="list-style-type: none"> <li>• 6.1m (20ft) of cable</li> <li>• Microphone hanger</li> <li>• Mounting base for connector</li> </ul> <p>Amber backlit COMMANDMIC, HM-195B/HM-195SW are also available.</p>	<p><b>EXTENSION CABLE for COMMANDMIC, HM-195GB/GW</b></p>  <p><b>OPC-1541</b> 6.1m (20ft) extension cable. Up to two cables available.</p>	<p><b>SPEAKER-MICROPHONE</b></p>  <p><b>HM-205B/SW</b> Same as supplied.</p>	<p><b>FLUSH MOUNT KIT</b></p>  <p><b>MB-132</b></p>	<p><b>CLASS B AIS TRANSPONDER</b></p>  <p><b>MA-500TR</b></p>
--	---	--	--	--

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia, Japan and/or other countries. COMMANDMIC, MarineCommander and AQUAQUAKE are trademarks of Icom Inc. (Japan). All other trademarks are the properties of their respective holders.

**Icom Inc.** 1-1-32, Kami-minami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 [www.icom.co.jp/world](http://www.icom.co.jp/world) **Count on us!**

**Icom America Inc.**  
12421 Willows Road NE,  
Kirkland, WA 98034, U.S.A.  
Phone: +1 (425) 454-8155  
Fax: +1 (425) 454-1509  
E-mail: [sales@icomamerica.com](mailto:sales@icomamerica.com)  
URL: <http://www.icomamerica.com>

**Icom (Europe) GmbH**  
Communication Equipment  
Auf der Krautweide 24  
65812 Bad Soden am Taunus, Germany  
Phone: +49 (6196) 76685-0  
Fax: +49 (6196) 76685-0  
E-mail: [info@icom-europe.com](mailto:info@icom-europe.com)  
URL: <http://www.icomeurope.com>

**Icom France s.a.s.**  
Zac de la Plaine,  
1 Rue Brindjonn des Moulinais, BP 45804,  
31505 Toulouse Cedex 5, France  
Phone: +33 (5) 61 36 03 03  
Fax: +33 (5) 61 36 03 00  
E-mail: [icom@icom-france.com](mailto:icom@icom-france.com)  
URL: <http://www.icom-france.com>

**Asia Icom Inc.**  
6F No. 68, Sec. 1 Cheng-Teh Road,  
Taipei, Taiwan, R.O.C.  
Phone: +886 (02) 2559 1899  
Fax: +886 (02) 2559 1874  
E-mail: [sales@asia-icom.com](mailto:sales@asia-icom.com)  
URL: <http://www.asia-icom.com>

Your local distributor/dealer:

**Icom Canada**  
Glenwood Centre #150-6165  
Highway 17A, Delta, B.C.,  
V4K 5B8, Canada  
Phone: +1 (604) 952-4266  
Fax: +1 (604) 952-0090  
E-mail: [info@icomcanada.com](mailto:info@icomcanada.com)  
URL: <http://www.icomcanada.com>

**Icom Spain S.L.**  
Ctra. Rubi, No. 88 "Edificio Can Castanyer"  
Bajos A 08174, Sant Cugat del Valles,  
Barcelona, Spain  
Phone: +34 (93) 590 26 70  
Fax: +34 (93) 589 04 46  
E-mail: [icom@icomspain.com](mailto:icom@icomspain.com)  
URL: <http://www.icomspain.com>

**Icom (Australia) Pty. Ltd.**  
Unit 1 / 103 Garden Road,  
Clayton, VIC 3168 Australia  
Phone: +61 (03) 9549 7500  
Fax: +61 (03) 9549 7505  
E-mail: [sales@icom.net.au](mailto:sales@icom.net.au)  
URL: <http://www.icom.net.au>

**Icom Brazil**  
Rua Itororó, 444 Padre Eustáquio  
Belo Horizonte MG,  
CEP: 30720-450, Brazil  
Phone: +55 (31) 3582 8847  
Fax: +55 (31) 3582 8967  
E-mail: [sales@icombrasil.com](mailto:sales@icombrasil.com)

**Icom (UK) Ltd.**  
Blacksole House, Altira Park,  
Herne Bay, Kent, CT6 6GZ, U.K.  
Phone: +44 (0) 1227 741741  
Fax: +44 (0) 1227 741742  
E-mail: [info@icomuk.co.uk](mailto:info@icomuk.co.uk)  
URL: <http://www.icomuk.co.uk>

**Icom New Zealand**  
39C Rennie Drive, Airport Oaks,  
Auckland, New Zealand  
Phone: +64 (09) 274 4062  
Fax: +64 (09) 274 4708  
E-mail: [inquiries@icom.co.nz](mailto:inquiries@icom.co.nz)  
URL: <http://www.icom.co.nz>