



THE AMERICAN BUILT-IN UNDERCOUNTER
MARKET LEADER SINCE 1962

MARINE/RV SERIES

LEISURE ON BOARD

For over five decades and three generations, U-Line continues to be known for innovation, clean lines and understated elegance. U-Line takes ice making to yet another environment. Our Marine/RV Series Models feature durability and good looks, as well as exceptional ice production and refrigeration capacity, for use above and below deck. Our U-Line Marine/RV ice makers are all manual defrost. They use less than 3 gallons of water to produce up to 25 lbs of ice so you'll never run out of ice with a minimal impact on fresh water reserves. There is no drain required and every U-Line Marine/RV ice maker comes with a positive catch door latch or travel pin so they are ready for the open sea or for storage. The corrosive-resistant, stainless steel hinges and fasteners on the durable and UV resistant cabinet and doors combine maximum convenience with durability and good looks.



Stainless



SS1095FC



SS1095FD



SS1095NF

SS1095

Marine/RV Series

- Daily crescent ice rate - up to 23 lbs
- Ice storage capacity - up to 12 lbs
- SS1095NF - no flange, can freestand
- SS1095FC - 1/2" mounting flange flush to cabinet
- SS1095FD - 1/2" mounting flange flush to door



White

WH95TP

Marine/RV Series

- Daily crescent ice rate - up to 23 lbs
- Ice storage capacity - up to 12 lbs
- 1/2" wide mounting flange



Black

BI95BTP

Marine/RV Series

- Daily crescent ice rate - up to 23 lbs
- Ice storage capacity - up to 12 lbs
- 1/2" wide mounting flange
- Accepts 1/4" Insert panel



SP18

Marine/RV Series

- Daily crescent ice rate - up to 23 lbs
- Ice storage capacity - up to 12 lbs
- 1/2" wide mounting flange
- Black model accepts 1/4" insert panel



White



Black



Stainless

SS98

Marine/RV Series

- Daily crescent ice rate - up to 25 lbs
- Ice storage capacity - up to 25 lbs
- Accepts 1/4" Insert panel



U-LINE

The American Built-In Undercounter Market Leader Since 1962



Stainless Black

1000 Series



Black White

Marine/RV Series

CO1175†

- Mechanical dial control
- Daily crescent ice rate - up to 18 lbs
- Ice storage capacity - up to 13 lbs
- Refrigeration capacity of 4.2 cubic feet
- Three tempered glass shelves and two door bins
- Black model will accept a 1/4" insert panel
- Manual defrost

CO29

- Daily crescent ice rate - up to 18 lbs
- Ice storage capacity - up to 13 lbs
- Refrigeration capacity of 2.1 cubic feet
- Two tempered glass shelves and door storage
- Black model will accept a 1/4" insert panel

SPECIFICATIONS

	Height (A) inches (mm)	Cabinet width (B) inches (mm)	Depth w/door † (C) inches (mm)	Depth w/o door (D) inches (mm)	Grille height (E) inches (mm)	**220/230V 50/60Hz CE mark	Run amps (110V)	Max start amps	Approx. shipping weight
MARINE/RV SERIES									
SSI095FD	25-7/8" (657mm)	13-15/16" (354mm)	16-15/16" (430mm)	15-3/32" (383mm)	8-7/8" (225mm)	220/230V CE	2.5	18.0	67 lbs (30 kg)
SSI095FC	25-3/16" (640mm)	13-15/16" (354mm)	16-15/16" (430mm)	15-3/32" (383mm)	8-13/16" (224mm)	220/230V CE	2.5	18.0	67 lbs (30 kg)
SSI095NF	24-3/4" (629mm)	13-15/16" (354mm)	16-15/16" (430mm)	15-3/32" (383mm)	8-13/16" (224mm)	220/230V CE	2.5	18.0	67 lbs (30 kg)
WH95TP	24-3/4" (629mm)	13-15/16" (354mm)	17" (432mm)	14-3/8" (365mm)	8-1/2" (216mm)	220/230V CE	2.4	18.0	66 lbs (30 kg)
BI95BTP	24-3/4" (629mm)	13-15/16" (354mm)	17" (432mm)	14-3/8" (365mm)	8-1/2" (216mm)	220/230V CE	2.4	18.0	66 lbs (30 kg)
SS98	27-3/8" (695mm)	14-15/16" (378mm)	20" (508mm)	17-3/8" (441mm)	8-3/4" (222mm)	220/230V CE	2.5	18.0	76 lbs (34 kg)
SPI8	18-1/2" (470mm)	13-15/16" (354mm)	24-13/16" (613mm)	22" (559mm)	2-13/16" (71mm)	220/230V CE	2.4	18.0	68 lbs (31 kg)
75F	34-1/8" (867mm)	23-15/16" (606mm)	23-3/16" (589mm)	20-7/8" (589mm)	3-1/8" (79mm)	220/230V CE	2.5	18.0	114 lbs (52 kg)
CO29	28-1/2" (724mm)	20-13/16" (529mm)	24" (630mm)	21-7/16" (545mm)	4-1/2" (114mm)	220/230V CE	2.5	18.0	98 lbs (44 kg)
1000 SERIES									
CO1175	34-1/8" (867mm)	34-1/8" (867mm)	23-1/4" (590mm)	21-7/16" (545mm)	3-1/8" (79mm)	220/230V CE	2.5	18.0	118 lbs (53 kg)
I175R	34-1/8" (867mm)	34-1/8" (867mm)	23-1/4" (590mm)	20-7/8" (530mm)	3-1/8" (79mm)	220/230V Non CE	2.4	9.8	110 lbs (50 kg)
29R	28-1/2" (724mm)	28-1/2" (724mm)	23" (584mm)	20-3/4" (527mm)	4-1/2" (114mm)	220/230V CE	2.4	9.8	89 lbs (40 kg)
I115R	34-1/8" (867mm)	34-1/8" (867mm)	22-7/8" (581mm)	20-3/4" (527mm)	3-1/8" (79mm)	220/230V Non CE	2.4	9.8	83 lbs (38 kg)

Specifications subject to change without notice. Sizes are for reference only.

For complete warranty, product catalog, detailed cutout, installation and panel specifications, electrical requirements and use & care information visit u-line.com

** At 220/230V, amps are decreased by approximately 50percent

Models CO1175 are intended for indoor/interior applications only and are not to be used in installations that are open/exposed to natural elements

